



公制规格表 (单位 MM):

螺纹	型号			A ± 0.13	B	W ± 0.1	L ± 0.25	C		L1	E	F
	铜	不锈钢	碳钢					热固性塑胶	热塑性塑胶			
M2*0.4	STB	STS	STC	4.72	3.1	0.51	5.8	3.28-3.23	3.24-3.17	6.76	3.58	0.81
M2.2*0.4	STB	STS	STC	4.72	3.1	0.51	5.8	3.28-3.23	3.24-3.17	6.76	3.58	0.81
M2.5*0.4	STB	STS	STC	5.54	3.35	0.64	7.57	3.96-3.86	3.86-3.78	8.76	4.37	1.07
M3*0.5	STB	STS	STC	6.35	4.32	0.76	9.02	5.03-4.93	4.93-4.83	10.46	5.56	1.27
M3.5*0.6	STB	STS	STC	6.35	4.32	0.76	9.02	5.03-4.93	4.93-4.83	10.46	5.56	1.27
M4*0.7	STB	STS	STC	7.14	4.95	0.89	9.15	5.84-5.74	5.74-5.63	10.82	6.35	1.27
M5*0.8	STB	STS	STC	9.53	5.89	1.02	10.27	6.86-6.71	6.71-6.58	12.19	6.86	1.42
M6*1.0	STB	STS	STC	11.13	7.67	1.14	11.69	8.71-8.53	8.58-8.38	14.15	9.53	1.6

美制规格表 (单位 inch):

螺纹	型号			B	A ± .005	W ± .004	L ± .010	C		L1	E	F
	铜	不锈钢	碳钢					热固性塑胶	热塑性塑胶			
2-56	STB	STS	STC	0.122	0.186	0.02	0.228	.129-.127	.127-.124	0.266	0.141	0.032
4-40	STB	STS	STC	0.132	0.218	0.025	0.298	.156-.152	.152-.149	0.345	0.172	0.042
6-32	STB	STS	STC	0.170	0.250	0.03	0.355	.198-.194	.194-.190	0.412	0.219	0.05
8-32	STB	STS	STC	0.195	0.281	0.035	0.36	.230-.226	.226-.222	0.426	0.25	0.05
10-24	STB	STS	STC	0.232	0.375	0.04	0.404	.270-.264	.264-.259	0.48	0.27	0.056
10-32	STB	STS	STC	0.232	0.375	0.04	0.404	.270-.264	.264-.259	0.48	0.27	0.056
1/4-20	STB	STS	STC	0.302	0.438	0.045	0.46	.343-.336	.336-.330	0.557	0.375	0.063
1/4-28	STB	STS	STC	0.302	0.438	0.045	0.46	.343-.336	.336-.330	0.557	0.375	0.063